



ART. 33/2611NHHV2

Diaphragm pumps - entirely in aluminum

Diaphragm pump series 1" 1000-AB in aluminum with membrane in NBR



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY
| MINING | SHIPPING AND OFFSHORE
WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Flow rate	l/min	170
Ratio		1:1
Compatible fluids		water, mineral-vegetable oils, diesel fuel
Pump material		aluminum
Ball valve material		Hytrel®
Air inlet connection		G 3/8" (f)
Fluid inlet-outlet connection		G 1.1/4" (f) x G 1" (f)
Air working pressure	bar	2 ÷ 6
Max supply pressure	bar	8
Average air consumption	l/min	1200
Noise level	dB	75
Fluid temperature	°C	-10 ÷ +90
Max solids diameter	mm	Ø 3
Suitable for drums or tanks		-
Suction-delivery ball valve with spring		ball valve with spring
Packing	N° - m³	1 - 0,025
Weight	kg	14
Dimensions (A-B-C)	cm	20 - 26 - 34,5
Suction tube length and Ø	cm	-

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2019 All rights reserved to RAASM S.p.A.