



ART. 3C1/50111NHH

Diaphragm pumps - entirely in aluminum

Diaphragm pump series 2" 2000-AB in aluminum with membranes in NBR, seats and balls in Hytrel®



FLUIDS

FRESH OIL | WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE
FRESH OIL | WATER

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Flow rate	l/min	610
Ratio		1:1
Max pressure	bar	8
Max cycles for minute	cpm	147
Delivery for cycles	litres	4,150
Max suction lift	m	dry column 5 - wet column 7,5
Max size pumpable solids	mm	6,5
Max working temperature	°C	100
Noise level	dB	82
Max air consumption	m³/min	4,00
Air working pressure	bar	2 ÷ 6
Air inlet connection		G 3/4" (f)
Air outlet connection (muffler)		G 1" (f)
Fluid inlet connection		G 2.1/2" (f)
Fluid outlet connection		G 2" (f)
Balls for inlet		ball valve
Membranes		NBR
Balls		Hytrel®
Seats		Hytrel®
Packing	N° - m³	1 - 0,12
Gross weight	kg	43

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2019 All rights reserved to RAASM S.p.A.